

We certify that Dymonic® 100 has been tested against ASTM C 920, Standard Specification for Elastomeric Joint Sealants and does conform to the specification requirements and is classified as follows:

Type: S	(Single Component)
Grade: NS	(Non-sag)
Class: 50	(+50% / - 50% joint movement)
Use: NT	(Non-traffic)
Use: T <sub>1</sub>	(Traffic)
M	(Mortar)
A	(Aluminum)
O	(Other)
I	(Immersion)

Additionally, we certify that Dymonic 100 has been tested in accordance to ASTM D 412, Test Method for Vulcanized Rubber and Thermoplastic Rubbers and Thermoplastic Elastomers – Tension, with the following results:

Ultimate Elongation: 850% - 1000%

We further certify that Dymonic 100 manufactured by Tremco Incorporated, Cleveland, Ohio conforms to the requirements of Federal Specification TT-S-00230C, Type II, Class A.

Dymonic meets CAN/CGSB 19.13, MCG-2-25-B-N.

Although Dymonic 100 is not NSF registered, or previously authorized by USDA, it does meet the requirements for use in Federally inspected food processing facilities provided it is not used in areas where food is being processed, prepared or packaged. The material must also be applied in a manner which prevents any direct or indirect contamination of food. Additionally, before any food product can be placed in the area of treatment, the sealant must be allowed to cure according to manufacturer's recommendations and the area should be sufficiently free of odor to prevent food contamination.