

| Vulkem® 346 | Vulkem® 351/or 351NF | Vulkem® 950NF | Vulkem® 951NF‡ | Vulkem® OC810 |
|---|---|---|--|---|
|  |  |  |  |  |
| BLACK (SPECIAL) | BLACK (SPECIAL) BLACK NF (SPECIAL) | BLACK | BLACK | BLACK (SPECIAL) |
|  |  |  |  |  |
| MAPLE | MAPLE MAPLE NF (SPECIAL) | MAPLE (SPECIAL) | MAPLE (SPECIAL) | MAPLE (SPECIAL) |
|  |  |  |  |  |
| BEIGE | BEIGE | BEIGE (SPECIAL) | BEIGE | BEIGE |
|  |  |  |  |  |
| SLATE GRAY | SLATE GRAY | SLATE GRAY | SLATE GRAY | SLATE GRAY |
|  |  |  |  |  |
| GRAY | GRAY | GRAY | GRAY | GRAY |
|  |  |  |  |  |
| LIMESTONE | LIMESTONE | LIMESTONE (SPECIAL) | LIMESTONE | LIMESTONE |
|  |  |  |  |  |
| WHITE (SPECIAL) | WHITE WHITE NF (SPECIAL) | WHITE (SPECIAL) | WHITE (SPECIAL) | WHITE (SPECIAL) |

Vulkem® 801 and Vulkem® 350NF & 360NF Base Coats Standard color for these base coats is Gray.

- Color deposits shown here are approximate and may not reflect sheen or shade precisely as varied amounts of aggregate added will alter light-reflecting properties. Tremco always recommends a test patch be done to gain final color approval.
- Custom colors are available. Minimum quantities apply.
- Plan 3 to 4 weeks minimum to color match, approve color, manufacture and ship product.

‡ *Vulkem 951NF is also available in Clear.*

Custom colors are made to order with a per-gallon up-charge in the following minimum quantities:

| Product | Minimum order | Package size | Pails/kits per order |
|--------------|---------------|--------------|----------------------|
| Vulkem 346 | 50 gal | 5-gal pails | 10 |
| Vulkem 351 | 5 gal | 5-gal pails | 1 |
| Vulkem 351NF | 50 gal | 5-gal pails | 10 |
| Vulkem 950NF | 200 gal | 4.2-gal kits | 48 |
| Vulkem 951NF | 80 gal | 4.6-gal kits | 18 |
| Vulkem OC810 | 800 gal | 5-gal pails | 160 |

PEDESTRIAN COATINGS

Tremco Pedestrian Deck Coating Systems are designed to create a moisture-curing, durable waterproofing membrane for plaza decks, pedestrian walkways, roof terraces, balconies, and plywood decks.

Vulkem® 350NF*/351 or 350NF*/351NF

Vulkem 350NF/351 is an attractive composite waterproofing system composed of tough-curing liquid polyurethane. Vulkem 351 also is available in a low-VOC neighbor friendly (NF) version.

Vulkem® 350NF*/951NF

Vulkem 350NF/951NF is a fast-curing, composite waterproofing system composed of tough-curing liquid polyurethane. In non-UV situations, Vulkem 950NF may be used in lieu of Vulkem 951NF.

VEHICULAR COATINGS

Tremco Vehicular Deck Coating Systems are designed for waterproofing concrete slabs and protecting occupied areas underneath from water damage. Additionally, these systems will protect the concrete from damaging effects of deicing salts, chemicals, gasoline, oils, and antifreeze.

Vulkem® 350NF*/950NF/951NF

Vulkem 350NF/950NF/951NF is a modified polyurethane traffic deck coating system composed of a base coat (350NF); an ultra-fast-curing, heavy duty intermediate coat (950NF); and a fast-curing top coat (951NF). This unique waterproofing system has tenacious adhesion, extreme impact and abrasion resistance along with remarkable chemical stability. Vulkem 951NF can be used for both the intermediate and top coats when extended pot life is needed, and Vulkem 950NF can be used for both coats in non-UV situations.

Vulkem® 350NF*/346/346**

Vulkem 350NF/346/346 is a modified polyurethane traffic deck coating system composed of a base coat (350NF), heavy duty intermediate coat (346) and top coat (346). This unique waterproofing system has tenacious adhesion, extreme impact and abrasion resistance, along with remarkable chemical stability.

** In all of these systems Vulkem 360NF can be used in place of 350NF.*

***Vulkem® 345 can be used as the intermediate coat in place of Vulkem 346.*

SPECIALTY COATINGS

Tremco offers durable waterproof coatings for a variety of specialty applications.

Vulkem® OC810

The Vulkem OC810 Coating is a high-solids, aliphatic urethane membrane developed to be applied in one 25-40-mil coat for aesthetically pleasing, waterproofing protection with excellent durability and UV resistance. It is low odor, low VOC (less than 30g/L), mildew- and fungus-resistant and designed for use with Tremco Rubber Aggregate 12-20 mesh for soft texture and skid-resistance. It is ideal for use on balconies, roof terraces, and mechanical rooms.

Vulkem® 801

Vulkem 801 is a liquid-applied, one-part polyurethane coating system that has been formulated to have a high tensile strength, tear strength and elongation all in a viscosity grade that can be used horizontally and vertically.



Produced with water-based paint and glue and vegetable oil-based ink to reduce VOCs and following green manufacturing practices including recycling of aluminum plates and other materials to keep waste out of landfills.