

OTRA Summary Plan for TDI

Toluene Diisocyanate CAS IDs:

Material as used by Tremco Canada Division, RPM Canada
220 Wicksteed Ave., Toronto, Ontario M4H 1G7

NIACS Codes:

Contacts

Ken McCallum – Environmental Coordinator
416-467-2447 ext. 2271
Sewnauth Raghunandan – HSE Manager
416-467-2447 ext. 2332
Paul Valadao – Director of Canadian Operations
416-467-2447 ext. 3499

Summary

The RPM Building Solutions Group (BSG) is committed to protecting the environment, preserving the health and safety of our employees and communities, and assuring the safe operations of our processes As such we continue to work to reduce the use of TDI.

Toluene Diisocyanate is used to create urethane polymers which are used for a variety of Waterproofing, Sealants, Adhesives and Coating materials.

Options Implemented

We continue to manage the use of TDI by using training and operating practices. This includes maintaining minimal on hand inventory and special instructions for handling isocyanates

Timelines

Because TDI is a fundamental component of products a reduction target of zero has been set. Reduction is zero therefore no timelines established

As of December 13, 2013 , I certify that I have read the toxic substance reduction plan for Toluene Diisocyanate and am familiar with its contents, and to my knowledge the plan is factually accurate and complies with the Toxics Reduction Act, 2009 Ontario Regulation 455/09 made under the act.

Paul A Valadao Paul A Valadao
Director of Canadian Operations
Dec 16 2013 Date