

Coatings Selection Guide

Vulkem® Coatings Solutions

Products		Extreme Wear	Under Tile	Pedestrian Deck	Vehicular Deck	Athletic Surface	Roof Terrace	Mechanical Room	Balconies	Low VOC	Below Freezing Temperature Application
Primer	Tremco PUMA Primer*	●	●	●	●	●	●	●	●	●	●
	Primer #171		●	●	●	●	●	●	●		
	Primer #191 QD		●	●	●	●	●		●	●	
Base Coat	Vulkem 350NF		●	●	●	●	●	●	●	●	
	Vulkem 360NF			●	●	●	●	●	●	●	
	Tremco PUMA BC*	●	●	●	●	●	●	●	●	●	●
	Tremco PUMA BC LM*	●	●	●	●	●	●	●	●	●	●
Intermediate Coat	Vulkem 345				●						
	Vulkem 346				●						
	Tremco PUMA WC*	●			●			●		●	●
	Vulkem 950NF	●			●			●		●	
Top Coat	Vulkem 346				●						
	Vulkem 351			●		●	●		●		
	Vulkem 351NF			●		●	●		●	●	
	Vulkem 950NF			●	●			●	●	●	
	Vulkem 951NF			●	●	●	●		●	●	
	Tremco PUMA TC*	●	●	●	●	●	●	●	●	●	●
Specialty	Vulkem OC810			●			●	●	●		

* These products are components of Vulkem EWS and should only be used in conjunction with each other, except when used for tying into Vulkem urethane coatings.

For specific tie-in recommendations and instructions, please contact your local Tremco Sales or Technical Service Representative.

NOTE: The Coatings Selection Guide is to be used as a general reference. Primer use will vary based on project requirements. Please consult your local Tremco Sales or Technical Service Representative for regional recommendations based on your local building practices and warranty requirements.

Reference the current product data sheet on our website at www.tremcosealants.com for more specific product information.

